

M201A

High Elasticity Acrylic-Styrene Copolymer Emulsion

Product Description

M201A High Elasticity Emulsion is an acrylic-styrene copolymer emulsion designed for high-elasticity sealants, exposed single-component waterproofing coatings, elastic coatings, and textured finishes. It is ideal for high-elasticity formulations with an emulsion-to-filler ratio ranging from 1:0.6 to 1. The cured material possesses silicone-like characteristics, presenting outstanding gloss, high water resistance, exceptional elongation, and high recovery. Additionally, it provides excellent anti-tack properties, high peel strength, and low-temperature flexibility below -20°C.

Product Features

- High gloss, high water resistance, high elongation, and excellent rebound recovery.
- Cured sealant strips possess silicone-like material characteristics.
- Excellent anti-tack performance, high pulling/peel strength, and outstanding low-temperature flexibility passing below -20°C.

Physical Properties*

Properties	Value	Unit	Test Method
Appearance	Milky white liquid with a slight blue tint	—	Visual
Solid Content	50 ± 1	wt%	GB/T 20623-2006

pH	8.0 - 9.0	—	GB/T 20623-2006
Viscosity	5000 - 9000	CPS	Brookfield DV-S, 4#, 30rpm, 25°C
Glass Transition Temperature (TG)	-20	°C	—

*Note: *The properties listed above represent typical results only and should not be construed as product specifications. Please refer to the specific Certificate of Analysis (COA) for official specifications.*

Storage

Please store this product in a cool, dry place away from direct sunlight. The storage temperature should be maintained between 5°C and 35°C. Keep the original packaging completely intact.

The shelf life of this product is six months from the date of manufacture. If the product exceeds its shelf life, a performance evaluation is highly recommended before use. Once the packaging is opened, it is recommended to filter the emulsion properly before application and consume it as quickly as possible.

Disclaimer

Shandong Sanjia Polymer Material Co., Ltd. strongly recommends that customers handle and use this product safely and rationally in accordance with the detailed information provided in the Material Safety Data Sheet (MSDS). While we believe the recommendations and data contained herein are true and reliable, the contents of this Technical Data Sheet are provided for reference purposes only. We offer no warranties, whether express or implied, regarding product characteristics, applications, quality, safety, product specifications, merchantability, or fitness for a particular purpose.

Shandong Sanjia Polymer Material Co., Ltd.