

M201C

High Elasticity Acrylic-Styrene Copolymer Emulsion

Product Description

M201C High Elasticity Emulsion is an acrylic-styrene copolymer emulsion designed for high-elasticity sealants, exposed single-component waterproofing coatings, elastic coatings, and textured finishes. The product delivers high gloss, exceptional water resistance, outstanding anti-tack performance, strong tensile pull strength, and low-temperature flexibility passing below -5°C.

Product Features

- High gloss and high water resistance.
- Excellent anti-tack performance and high pulling/peel strength.
- Outstanding low-temperature flexibility passing below -5°C.

Physical Properties*

Properties	Value	Unit	Test Method
Appearance	Milky white liquid with a slight blue tint	—	Visual
Solid Content	50 ± 1	wt%	GB/T 20623-2006
pH	7.5 - 8.5	—	GB/T 20623-2006
			Brookfield DV-S, 4#,

Viscosity	2000 - 4000	CPS	30rpm, 25°C
Glass Transition Temperature (TG)	-5	°C	—

*Note: *The properties listed above represent typical results only and should not be construed as product specifications. Please refer to the specific Certificate of Analysis (COA) for official specifications.*

Storage

Please store this product in a cool, dry place away from direct sunlight. The storage temperature should be maintained between 5°C and 35°C. Keep the original packaging completely intact.

The shelf life of this product is six months from the date of manufacture. If the product exceeds its shelf life, a performance evaluation is highly recommended before use. Once the packaging is opened, it is recommended to filter the emulsion properly before application and consume it as quickly as possible.

Disclaimer

Shandong Sanjia Polymer Material Co., Ltd. strongly recommends that customers handle and use this product safely and rationally in accordance with the detailed information provided in the Material Safety Data Sheet (MSDS). While we believe the recommendations and data contained herein are true and reliable, the contents of this Technical Data Sheet are provided for reference purposes only. We offer no warranties, whether express or implied, regarding product characteristics, applications, quality, safety, product specifications, merchantability, or fitness for a particular purpose.

Shandong Sanjia Polymer Material Co., Ltd.